

TECHNICAL BULLETIN

SUBJECT: ETL Trim (Cylinders by Others)

TECHNICAL BULLETIN ID: E080717-01

DATE: 08/7/17

The ETL trim series comes with a 1-1/4" mortise cylinder. The cylinder is a Schlage "C" keyway. It comes drilled & pinned 6 pin. Below are the instructions to use standard cylinders and I/C housings by others.

Standard Mortise Cylinder

Use a 1-1/4" cylinder with an A/R cam. Use ILCO's 7205 in your preferred keyway and finish. Swap the standard cam for their A/R cam (863A). Use a lock/cash nut from Von Duprin (VON 971974) to secure the housing in the trim.

SFIC and LFIC Mortise Cylinder Housings

For SFIC use Schlage's 80-108 housing. For Schlage's LFIC use the 30-137 or 30-007 housing only or the 26-091 housing with core. Swap the cam for any of the units listed above with the K510-711 A/R cam for I/C housings. Disregard any collars and or spacers that came with the housing by others. Use the 3/4" collar that comes with the Doormerica trim along with a 1/8" spacer (ILCO 861D). The original collar along with the 1/8" spacer will give the correct depth for the housing to be installed in the trim, put the collar on first and then the spacer. Use a lock/cash nut from Von Duprin (VON 971974) to secure the housing in the trim.

